

8F3011-Z



Images are for reference only. See Product Specifications for product details. Buy 8F3011-Z with confidence from Components-Store.com, 1 Year Warranty



Part Number: 8F3011-Z

Manufacturer Copal Electronics

Description SWITCH TOGGLE 3PDT 6A 125V

Data sheet: 📷 8F Series

RoHs Status: Lead free / RoHS Compliant

Ship From: Hong Kong

Shipment Way: DHL/Fedex/TNT/UPS/EMS

Request For Quotation

PRODUCT PARAMETER

Parkumber90012ParkumberConditionationationationationationationation			
DescriptionSWTCH TOGGLE SPDT A 125VLad Free Status / RoHS StatusLad Free Status / RoHS CompiantGuarty Available1065 pcProduct Photo1065 pcProduct PhotoSectradsCategorySectradsVoltage Rating - ACSchool School	Part Number		<u>8F3011-Z</u>
Lead Pre-Status / RottS StatusLead the / RottS Complant.Quantity Available4486 pppPoduct PhotoBrith 2 LosCalegorySelfchareVatage Rating - DCSelfchareVottage Rating - AC129VTermination SkyleSolder LugSwitch FunctionOn-OnBenkareOn-OnBenkareOn-OnBenkareSolder LugOutsper Rating - ACOn-OnBenkareOn-OnBenkareOn-OnBenkareSolder LugPanel Court DimensionsGracuar - 6.0mm DiaPonce Court DimensionsSolder LugOperating TemperatureSolder ComplantOperating TemperatureSolder Panel ComplantMaining TypeNational Solder ComplantInternistion Voltage (Normal)InternistionInternistion Voltage (Normal)Solder Pred ComplantInternistion Voltage (Normal)Solder Pred ComplantBeaching StraigSolder ComplantInternistion Volt	Manufacturer		Copal Electronics
Quantity Available10455 pcsProduct Phore#2011.7 LineProduct PhoreBailentrageQuantity AvailableBailentrageVottage Rating - OC30%Vottage Rating - AC30%Vottage Rating - ACSolden LugTermination StyleBolen LugSeriesBailent FunctionPerclaint FunctionOn OnPerclaint FunctionOn OnPerclaint FunctionOn OnPerclaint FunctionOn OnPerclaint StyleBuiltOperating TemperatureBuiltOperating Temperature2010 - 05°CMounting TypeParal MountMounting TypeInformationIndextor StatusEast Production (MSL)Least Production (MSL)InformationInternation Type, ColorInformationInternation Type, ColorSouto SpreamInternation Type, ColorSouto SpreamPerclaind Terme AvailableSouto SpreamPerclaind Type, ColorSouto SpreamInternation Type, ColorSouto SpreamInternation Type, ColorSouto SpreamPerclaind DescriptionSouto SpreamPerclaind DescriptionSouto SpreamOutor Rating ThreadSpreamDescriptionSouto SpreamGuard Type, ColorSouto SpreamDescriptionSouto SpreamDescriptionSouto SpreamDescriptionSpreamDescriptionSpreamDescriptionSpreamDescriptionSpream <th>Description</th> <th></th> <th>SWITCH TOGGLE 3PDT 6A 125V</th>	Description		SWITCH TOGGLE 3PDT 6A 125V
Product PhotoBEGUT.2 LineCalegorySwitchingVoltage Rating - DCSWItchingVoltage Rating - DCSWItchingVoltage Rating - AC125VTermination StyleScider LugSwitching - ACScider LugSwitching - ACScider LugSwitching - DCOnSwitching - DCScider LugSwitching - DCScider LugIturnisation Type, ColorScider LugIturnisation Type, ColorScider LugSwitching - DCScider LugSwitching - DCSc	Lead Free Status / RoHS Statu	S	Lead free / RoHS Compliant
CategorySwitcheVotage Rating - DCSolvVotage Rating - ACSolvTermination StyleSolder LugSwitch FunctionOn-OnSwitch FunctionOn-OnSwitch FunctionOn-OnSwitch FunctionOn-OnPenel Colud DimensionsOn-OnPenel Colud DimensionSolver ColumensionPostagingBarkOther NamesSolver ColumensionOperating TemperatureSolver ColumensionMouting TypeQuality ColumensionMouting TypeQuality ColumensionIngress ProtectionSolutan ColumensionIngress ProtectionSolutan ColumensionIngress ProtectionSolutan ColumensionInternation Votage (Nomisi)ColumensionInternation Votage (Nomisi)Solutan ColumensionInternation Votage (Nomisi)Solutan ColumensionInternation Votage (Nomisi)Solutan ColumensionElectrical LifeSolutan ColumensionDescriptionSolutan ColumensionCurrent RatingSolutan ColumensionCurrent RatingSolutan ColumensionChront Rating TreadSolutan ColumensionRekutor TypeSolutan ColumensionRekutor TypeSolutan ColumensionCurrent Rating ColumensionSolutan ColumensionCurrent RatingSolutan ColumensionCurrent Rating ColumensionSolutan ColumensionCurrent Rating ColumensionSolutan ColumensionCurrent Rating ColumensionSolutan ColumensionCurrent	Quantity Available		10485 pcs
Votage Rating - DC30VVotage Rating - AC123VTermination Style3older LigSwitch FunctionOn-OnSwitch FunctionOn-OnSeriesSeriesPace Quoter DimensionsGiscular - 8.50mm DiaPace Quoter DimensionsBuikOperating Temperature-20°C - 85°CMouting TypeQuoter Store Status / RoHS StatusInstrume Status / RoHS Status-20°C - 85°CInstrume Status / RoHS Status-20°C - 80°CInstrume Status / RoHS Status-20°C - 80°C - 80°CInstrume Status / RoHS Status-20°C - 80°C - 80°CInstrume Status / RoHS Status-20°C - 80°C - 80°C - 80°CInstrume Status / RoHS Status-20°C - 80°C - 80	Product Photo		<u>8F3011-Z.jpg</u>
Votage Rating - AC125VTermination StyleSolder LugSwitch FunctionOn-OnSwitch FunctionOn-OnPanel Cutout DimensionsGrouder - 0.50mm DiaPanel Cutout DimensionsOlivel - 0.50mm DiaPackagingBulkOher NamesGostart - 0.50mm DiaOperating TemperatureSolder - 0.50mm DiaMouting YapePanel MountInstarter Statistivity Level (MSL)Itulinitoit)Instarter Statistivi	Category		Switches
Termination SyleSolder LugSwitch FunctionOn-OnSeriesSeriesPanel Cutota DimensionsDiradar - Scorna DiaPackagingSila 173Oter NamesSolder Scorna DiaOperating TemperatureSolder Scorna DiaMatter Status TemperatureSolder Scorna DiaIndicator Status TemperatureSolder Scorna DiaMatter Status TemperatureSolder Scorna DiaIndicator TemperatureSolder Scorna DiaIndicator Status TemperatureSolder Scorna DiaIndicator Status TemperatureSolder Scorna DiaIndicator Temperatur	Voltage Rating - DC		30V
Switch FunctionOn-OnSeriesGenomePanel Cutout DimensionsCrouter - 8.0mm DiaPackagingBukOther NamesGonomOperating TemperatureBukMounting TypePanel MountMotatur Sensitivity Lovel (MSL)Conder / Rolfs CompliantIndestore Sensitivity Lovel (MSL)Conder / Rolfs CompliantIndimination Voltage (Mominal)Anolf MountIllumination Type, ColorAnolf MountIllumination Type, ColorAnolf MountIndimination Type, ColorAnolf MountIndimination Type, ColorAnolf MountIndimination Type, ColorSignet MountIndimination Type, ColorAnolf MountIndimination Type, ColorSignet MountIndimination Type, ColorSignet MountIndimination Type, ColorSignet MountIndiminationAnolf MountIndiminationSignet M	Voltage Rating - AC		125V
SeriesSeriesPael Cutout DimensionsCircular - 6.50mm DilaPaelagingBulkOther NamesS03-713Other Names- 20°C - 8°CParel TypePanel MourtMonting TypePanel MourtIndisture Sensitivity Level (MSL)Lead Free Status / RoHS StatusIndistor Softer StatusCarder For Status / RoHS StatusIndination Vortage (Nominal)- 20°C - 8°CIndination Vortage (Nominal)- 20°C - 8°CIndination Type, Color- 20°C - 8°CIndination- 20°C - 8°CIndination- 20°C - 8°CIndination- 20°C - 8°CIndination- 20°C - 8°CIndication Status (Status - 8°C)- 20°C -	Termination Style		Solder Lug
Parl Cutout DimensionsCircular - 6.50mm DilaPackagingBukOther NamesSi3-1713Operating TemperatureSi2-06 - 65°CMouting TypeBanel MountInstare Sensitivity Level (MSL)Circuler - 64°CIngress ProtectionSplash ProfeInfuniation Voltage (Nominal)Splash ProfeInfuniation Voltage (Nominal)Sill Sill Sill Sill Sill Sill Sill Sill	Switch Function		On-On
PackagingBukOther Names68-1713Operating Temperature20°C ~ 85°CMounting TypePanel MountMounting Type10 (Initiated)Lead Free Status / RoHS StatusGad free / RoHS CompliantIngress ProtectionSpain ProofIllumination Voltage (Nominal)-Illumination Type, Color-Illumination Type, ColorNon-IlluminatedIndicated Lead Free Status / RoHSNon-IlluminatedIllumination Type, Color-Illumination Type, ColorSignite Status / Signite StatusIllumination Type, ColorNon-IlluminatedIllumination Type, ColorSignite Status / Signite StatusIllumination Type, ColorNon-IlluminatedIllumination Type, ColorSignite Status / Signite StatusIllumination Type, ColorSignite Status	Series		8F
Other Names563-713Operating Temperature20°C - 8°CMounting TypePanel MountMoisture Sensitivity Level (MSL)1 (Unimiled)Laad Free Status / RoHS StatusLead free / RoHS CompliantIngress ProtectionSplash ProofIllumination Votage (Nominal)-Illumination Type, Color-Illumination Type, ColorNon-IlluminatedFeatures-Illumination-Electrical LifeSono CyclesDetailed DescriptionGood CyclesCurrent Rating-Bushing Thread-Austor Type-Austor Typ	Panel Cutout Dimensions		Circular - 6.50mm Dia
Operating Temperature-20°C ~ 8°CMounting TypePanel MountMouting TypePanel MountMotature Sensitivity Level (MSL)1 (Unlimited)Lead Free Status / ROHS StatusLead free / ROHS CompilantIngress ProtectionSplase ProdeIllumination Voltage (Nominal)-Illumination Type, Color-Illumination Type, ColorNon-IlluminatedFeatures-IlluminationSplase ProdeDetailed DescriptionSplase Not OccupiedCurrent RatingSplase Not OccupiedGrudtSplase Not OccupiedIllumination Type, ColorSplase Not OccupiedSplase Not OccupiedSplase Not OccupiedIlluminationSplase Not Occupie	Packaging		Bulk
Mouting Type Panal Mounting Type Moisture Sensitivity Level (MSL) (Unlimited) Lead Free Status / RoHS Status Lead Free Nath Schuppiant Ingress Protection Splash Proof Illumination Voltage (Nominal) - Illumination Type, Color - Illumination Type, Color - Electrical Life Non-Illuminated Electrical Life S000 Cycles Electrical Life Sologi Switch SPDT Panal Mount Corrent Rating A(A)(A, A (DC) Bushing Thread SPDT Actuator Type Status Type Actuator Type Status Type	Other Names		563-1713
Moisture Sensitivity Level (MSL) 1(Unimited) Lead Free Status / RoHS Status Lead Free Chills Compliant Ingrees Protection Splash Proof Illumination Voltage (Nominal) - Illumination Type, Color - Illumination Non-Illuminated Features - Electrical Life Splash Prodeutout Current Rating Color (Color (Col	Operating Temperature		-20°C ~ 85°C
Lead Free Status / RoHS Status Lead free / RoHS Compliant Ingress Protection Splash Proof Illumination Voltage (Nominal) - Illumination Type, Color - Illumination Type, Color Non-Illuminated Features Non-Illuminated Electrical Life 5,000 Cycles Iclumination Cycles Current Rating Gale Status / Rohd Iclumination Splash Type Index Iclumination Splash Status Iclumination Splash Status <th>Mounting Type</th> <th></th> <th>Panel Mount</th>	Mounting Type		Panel Mount
Ingress Protection Splash Proof Illumination Voltage (Nominal) - Illumination Type, Color - Illumination Non-Illuminated Features Non-Illuminated Detailed Description 5000 Cycles Current Rating GalXAL (CO) Icruit Splashing Thread Atuator Type Atuator Type	Moisture Sensitivity Level (MS	L)	1 (Unlimited)
Illumination Voltage (Nominal)-Illumination Type, Color-Illumination Type, ColorNon-IlluminatedIlluminationNon-IlluminatedFeatures-Electrical Life5,000 CyclesDatailed DescriptionToggle Switch 3PDT Panel MountCircuitACA), 4A (DC)Bushing Thread14-40Actuator TypeStandard RoundActuator TypeStandard Round	Lead Free Status / RoHS Statu	S	Lead free / RoHS Compliant
Ilumination Type, Color-Ilumination Type, ColorNon-IluminatedIluminationNon-IluminatedFeatures-Electrical LifeS0,000 CyclesDetailed DescriptionTogle Switch 3PDT Panel MountCurrent RatingA(C), 4A (DC)CircuitSPTBushing Thread14-40Actuator TypeStandard RoundActuator TypeStandard Round	Ingress Protection		Splash Proof
IlluminationNon-IlluminatedFeatures-Electrical Life50,000 CyclesDetailed DescriptionTogle Switch 3PDT Panel MountCurrent Rating6A (AC), 4A (DC)CircuitSpDTBushing Thread1/4-40Actuator TypeStandard RoundActuator MaterialScholar Scholar Sch	Illumination Voltage (Nominal)		-
Features-Electrical Life5,000 CyclesDetailed DescriptionTogle Switch 3PDT Panel MountCurrent Rating6A (C), 4A (DC)Circuit3PDTBushing Thread1/440Actuator TypeSandard RoundActuator Material-	Illumination Type, Color		-
Electrical Life50,000 CyclesDetailed DescriptionTogle Switch 3PDT Panel MountCurrent Rating6A (AC), 4A (DC)Circuit3PDTBushing Thread1/4-40Actuator TypeStandard RoundActuator Material50,000 Cycles	Illumination		Non-Illuminated
Detailed Description Togle Switch 3PDT Panel Mount Current Rating 6A (AC), 4A (DC) Circuit 3PDT Bushing Thread 1/4-40 Actuator Type Standard Round Actuator Material	Features		-
Current Rating6A (AC), 4A (DC)Circuit3PDTBushing Thread1/4-40Actuator TypeStandard RoundActuator Material-	Electrical Life		50,000 Cycles
Circuit3PDTBushing Thread1/4-40Actuator TypeStandard RoundActuator Material-	Detailed Description		Toggle Switch 3PDT Panel Mount
Bushing Thread 1/4-40 Actuator Type Standard Round Actuator Material -	Current Rating		6A (AC), 4A (DC)
Actuator Type Standard Round Actuator Material -	Circuit		3PDT
Actuator Material -	Bushing Thread		1/4-40
	Actuator Type		Standard Round
Actuator Length 10.50mm	Actuator Material		-
	Actuator Length		10.50mm

Components-Store.com is a Reliable Stocking Distributor of Electronic Components. We specialize in all Copal Electronics series electronic components. We have 10485 pieces of Copal Electronics 8F3011-Z in stock available now. Request a quote from electronics components distributor at Components-Store.com, our sales team will contact you within 24 hours. RFQ Email: info@Components-Store.com

RELATED PRODUCTS

0000	Part#: 2-1825137-0	Manufacturers: Agastat Relays / TE Connectivity	RFQ	
>	Description: SWITCH TOGGLE SPDT 5A 120V	In Stock: 22646		
C &K	Part#: 7405P3Y9CKE Description: SWITCH TOGGLE 4PDT 0.4VA 20V	Manufacturers: C&K In Stock: 6922	RFQ	
	Part#: 8F36-AAA105-1.00 Description: HI RTBLTY INT MINI SAS CBL ASSY	Manufacturers: 3M In Stock: 10514	RFQ	
Honeywell	Part#: 11TW8-5M	Manufacturers: Honeywell Sensing and Productivity Solutions	RFQ	
	Description: SWITCH TOGGLE SPDT 5A 125V	In Stock: 803		
Q.	Part#: 8F36-AAC305-0.50	Manufacturers: 3M	RFQ	
1	Description: CABLE MINI SAS 36POS NO SB 0.5M	In Stock: 15217		
C.K	Part#: 7201L2PD9V7BE	Manufacturers: C&K	RFQ	
Uan	Description: SWITCH TOGGLE DPDT 0.4VA 20V	In Stock: 8021		

зм	Part#: 8F36-AAC305-1.00	Manufacturers: 3M	RFQ
Authorized Distributor	Description: HI RTBLTY INT MINI SAS CBL ASSY	In Stock: 5257	
	Part#: 100SP1T2B2M1QE	Manufacturers: E-Switch	RFQ
E-SWITCH	Description: SWITCH TOGGLE SPDT 5A 120V	In Stock: 54177	
C.K	Part#: 7201SHCGES	Manufacturers: C&K	RFQ
UAN	Description: SWITCH TOGGLE DPDT 5A 120V	In Stock: 12045	
C.K	Part#: 7201MYCBE2	Manufacturers: C&K	RFQ
UAN	Description: SWITCH TOGGLE DPDT 0.4VA 20V	In Stock: 8160	
C.K	Part#: 7101P3Y9A3LE	Manufacturers: C&K	RFQ
Uan	Description: SWITCH TOGGLE SPDT 5A 120V	In Stock: 10449	
	Part#: S822/C	Manufacturers: NKK Switches	RFQ
SWITCHES	Description: SWITCH TOGGLE DPDT 30A 125V	In Stock: 4158	
18	Part#: 7401P3DV8BE2	Manufacturers: C&K	RFQ
8	Description: SWITCH TOGGLE 4PDT 0.4VA 20V	In Stock: 5377	
\mathcal{O}	Part#: 8F36-AAA105-0.50	Manufacturers: 3M	RFQ
1	Description: CABLE MINI SAS 36POS 0.5M	In Stock: 14813	
C.K	Part#: 7107T1CWCBI	Manufacturers: C&K	RFQ
Uan	Description: SWITCH TOGGLE SPDT 0.4VA 20V	In Stock: 11249	
C.V	Part#: 7405P3YZQES	Manufacturers: C&K	RFQ
UAN	Description: SWITCH TOGGLE 4PDT 5A 120V	In Stock: 5153	
C.V	Part#: 7201P3YAGE	Manufacturers: C&K	RFQ
UAN	Description: SWITCH TOGGLE DPDT 5A 120V	In Stock: 7308	
	Part# SV237CD7	Manufacturers: APEM Inc	

Manufacturers: APEM Inc.

PEO

	Copal Electron	ics 8F3011-Z	8F3011-Z distributor	8F3011-Z supplier	8F3011-Z price	
Related keywords for 8F3011-Z						
		Description: SWITCH TOGGLE 4PDT 5A 120V		In Stock: 3945		
	C.e.K			Manufacturers: C&K		RFQ
		Part#: 7405T2PZGE	Ma	nufacturere: C&K		
000		Description: SWITCH TOGGLE DPDT 15A 125V		In Stock: 10053		
	-	Part#: S29AW	Ma	nufacturers: NKK Switches		RFQ
		Description: SWITCH TOGGLE SPD	DT 0.4VA 20V In S	Stock: 14853		
	O APEM					T C C

8F3011-Z download datasheet	8F3011-Z datasheet	8F3011-Z stock	buy 8F3011-Z
Copal Electronics 8F3011-Z	Copal Electronics Inc. 8F3011-Z	Nidec Copal Electronics 8F3011-Z	

Reliable Stocking Distributor of Electronic Components © 2003-2019 Components-Store.com All Rights Reserved. E-mail: info@Components-Store.com



