



Part Number: 8720

Single-Pair, (1 pr) 14 AWG (19x27) TC, PE/PVC, Foil Shld

# Request Sample

### **Product Description**

One 14 AWG pair stranded (19x27) TC conductors, twisted pair, polyethylene insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

## **Technical Specifications**

### **Physical Characteristics (Overall)**

Conductor				
AWG	Stranding	Material	No. of Pairs	
14	19x27	TC - Tinned Copper	1	
Conductor Count:				
Total Number of Pairs:				
Conductor Size:				

### Insulation

Material	Nominal Wall Thickness
PE - Polyethylene	0.032 in

### Color Chart

Number	Color
1	Black & Clear

### Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Таре	Aluminum/Polyester	Beldfoil® (Z-Fold®)	100 %	TC - Tinned Copper	16	Stranded mm

### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.355 in	0.035 in

## **Electrical Characteristics**

### Conductor DCR

Nominal Conductor DCR
2.9 Ohm/1000ft

### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
24 pF/ft	47 pF/ft
Shielding:	Foil(s) or Copper Tape(s)

### Inductance

Nominal Inductance 0.2 µH/ft

### Impedance

Nominal Characteristic Impedance 58 Ohm

### Current

# Max. Recommended Current [A] 9.5 Amps per conductor @ 25°C

## Voltage

Non-UL Voltage Rating	UL Description	UL Voltage Rating
300 V RMS	UL AWM Style 20253	600 V RMS
	CSA	300 V RMS

## **Temperature Range**

UL Temp Rating:	80°C (UL AWM Style 20253)
Operating Temp Range:	-20°C To +80°C

## **Mechanical Characteristics**

Bulk Cable Weight:	64 lbs/1000ft
Max Recommended Pulling Tension:	160 lbs
Min Bend Radius/Minor Axis:	3.75 in

## **Standards**

NEC Articles:	800
NEC/(UL) Specification:	CL2
CEC/C(UL) Specification:	AWM II A
UL AWM Style:	UL Style 20253 (600 V 80°C)
CPR Euroclass:	Eca

## **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
CSA Flammability:	FT1
UL voltage rating:	600 V RMS

## Plenum/Non-Plenum

	Plenum (Y/N):	No

## **Part Number**

## Variants

Item #	Color	Footnote
8720.00305	Chrome	
8720 0601000	Chrome	С
8720 0602000	Chrome	С
8720 060500	Chrome	С
8720 0605000	Chrome	С
8720 060U500	Chrome	

	Footnote:	C - CRATE REEL PUT-UP.
--	-----------	------------------------

#### © 2018 Belden, Inc

### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.